


CS 186 Spring 1994 Midterm Professor Gunther A. Vahdat

Problem #1 (15 Credits)

Suppose you are database administrator at a large university that is (still) using a hierarchical database system. You have chosen the following scheme to represent information about its faculty, students, departments, and courses.



Dept	dno	dname		
Student	sno	sname	classyr	
Prof	pno	pname	salary	
Course	cno	title		
Chair	pno	pname	salary	
Enroll	sno	sname	classyr	grade

Problem #2 (15 Credits)

Let R denote a relational database scheme and F a set of functional dependencies defined on R . Furthermore, let G denote a minimal cover of F .

- (a) Prove that any attribute that does not appear in any functional dependency in G belongs to every key of R .
- (b) Prove that if there is a functional dependency in the minimal cover G in which all attributes of R appear, then R is in third normal form with respect to F .

Problem #3 (15 Credits)

Give an example for a relational database scheme R and a set F of functional dependencies defined on R , such that

- (i) R is not in third normal form (3NF) with respect to F , and
- (ii) there are at least two ways to decompose R into a *minimum number* of relations R_1, \dots, R_k such that each R_i is in 3NF with respect to the corresponding projection of F , and the decomposition has a lossless join and preserves dependencies.

Give at least two of the possible 3NF-decompositions.

Problem #4 (15 Credits)

Consider the relational database scheme $R = ABCD$ with a set of functional dependencies $F := \{AB \rightarrow C, BC \rightarrow D\}$.

- Give all candidate keys for R (with respect to F).
- Show that R is not in 3NF (with respect to F).
- Find a 3NF-decomposition of R that has a lossless join, preserves dependencies, and consists of a minimum number of relations.
- Is $G := \{AB \rightarrow C, AB \rightarrow D\}$ a minimal cover of F ? Prove your answer.

Problem #5 (10 Credits)

Give an example of a view built on the relation $EMP(\text{name, salary, age, dept, manager})$ and two updates for that view which cannot be unambiguously translated to updates on the underlying base relation. Credit will be awarded proportional to the complexity of your examples.

Problem #6 (20 Credits)

Consider the relations

HOUSE(house-id, h-address, h-age)

PERSON(person-id, p-name, p-age)

OWNS(house-id, person-id)

LIVES-IN(house-id, person-id)

with the condition that a person can live in and own multiple houses. Write SQL queries for the following tasks. Credit will be awarded inversely proportional to the complexity of your queries.

- Find the names of people who are part or full owners of at least one of the houses in which they live.
- Find the name of the person who owns the most houses.
- Find the names of the people who do not live anywhere.
- Find the names of all people who live in a house which is the same age as the person's age.

Posted by HKN (Electrical Engineering and Computer Science Honor Society)

University of California at Berkeley

**If you have any questions about these online exams
please contact <mailto:examfile@hkn.eecs.berkeley.edu>**